

# MATERIAL SAFETY DATA SHEET

## COPPER-NICKEL-ZINC ALLOYS 731, 733, 742, 752, 758, 762, 770

Page 1 of 7

### 1.0 PRODUCT AND COMPANY IDENTIFICATION

PMX Industries, Inc.  
5300 Willow Creek Drive SW  
Cedar Rapids, Iowa 52404-4303

Emergency: 319-368-7700

TELEPHONE: 319-368-7700

FAX: 319-368-7701

PRODUCT NAMES:	PMX ALLOY #	COMMON NAME	UNS #/CDA #
	731		C73110
	733		C73300
	742		C74210
	752	Nickel Silver 65-18	C75200
	758		C75800
	762	Nickel-Silver 70-12	C76200
	770	Nickel-Silver 59-18	C77000

CHEMICAL FAMILY: Copper Alloy

ISSUE DATE: December 15, 2004

SUPERSEDES DATE: May 13, 1999

### 2.0 HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

Copper alloy products in the natural state do not present a hazard for emergency response personnel.

#### POTENTIAL HEALTH EFFECTS:

Copper alloy products in the natural state do not present an inhalation, ingestion, or contact hazard. However, operations such as burning, welding, sawing, brazing, or grinding may release fumes and/or dusts which may present health hazards if occupational exposure limits are exceeded.

# MATERIAL SAFETY DATA SHEET

## COPPER-NICKEL-ZINC ALLOYS 731, 733, 742, 752, 758, 762, 770

Page 2 of 7

**LIKELY ROUTES OF EXPOSURE:** Inhalation, Eye Contact, Skin Contact

**INHALATION:** Short-term exposure to fumes/dust may produce irritation of the respiratory system. Exposure to high concentrations of copper or zinc oxide fumes may cause metal fume fever.

**EYE:** Short-term exposure to fumes/dust may produce irritation.

**SKIN:** Repeated or prolonged exposure to copper dusts or mists may cause irritant or allergic contact dermatitis.

**INGESTION:** Ingestion of large doses of nickel compounds (1-3 mg/kg) has been shown to cause intestinal disorders, convulsions, and asphyxia.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Exposure to fumes or dust may aggravate existing respiratory disease or dermatitis.

**TARGET ORGANS:** Upper respiratory tract, eyes, skin

### SIGNS AND SYMPTOMS:

Metal fume fever – metallic taste in mouth, dryness, and irritation of the throat, and influenza-like symptoms. The effects may be delayed.

Nickel overexposure – effects on nasal sinuses, including inflammation and ulceration.

### CARCINOGENICITY:

COMPONENT	ACGIH	IARC	NTP
Copper (fume, dusts & mists)	No	No	No
Nickel	No	Yes	Yes
Zinc oxide fume	No	No	No

See Toxicological Information (Section #11)

### POTENTIAL ENVIRONMENTAL EFFECTS:

None known. Product has not been tested for environmental properties.

## 3.0 CHEMICAL COMPONENTS

NOTE: This MSDS applies to a range of alloys. For actual compositions refer to material test report or specific alloy specification. All percentages are by weight.

COMPONENT	CAS #	%
Copper	7440-50-8	53.5 – 73.5
Nickel	7440-02-0	2 – 21
Zinc	7440-66-6	13 – 32

# MATERIAL SAFETY DATA SHEET

## COPPER-NICKEL-ZINC ALLOYS 731, 733, 742, 752, 758, 762, 770

Page 3 of 7

### 4.0 FIRST AID MEASURES

**INHALATION:** If exposed to excessive levels of metal fumes, remove to fresh air. Seek medical attention.

**EYE:** Flush with water for at least 15 minutes.

**SKIN:** Wash with soap and water.

### 5.0 FIRE FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Use extinguishing media appropriate to the surrounding material.

**SPECIAL FIREFIGHTING INSTRUCTIONS:** Copper alloy products in the solid state present no fire or explosion hazard, but may react with strong acids, bases, or oxidizing agents.

### 6.0 ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN THE EVENT OF SPILLS, LEAKS, OR RELEASES:** Not applicable

### 7.0 HANDLING AND STORAGE

**HANDLING:** In welding, precautions should be taken for airborne contaminants that may originate from components of the welding rod.

### 8.0 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### EXPOSURE GUIDELINES

COMPONENT	OSHA PEL TWA	ACGIH® TLV® TWA	ACGIH® TLV® STEL
Copper dust, mist	1.0 mg/m <sup>3</sup>	1.0 mg/m <sup>3</sup>	not established
Copper fume	0.1 mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup>	not established
Nickel, elemental	1.0 mg/m <sup>3</sup>	1.5 mg/m <sup>3</sup> I	not established
Zinc oxide	5.0 mg/m <sup>3</sup>	2.0 mg/m <sup>3</sup> R	10.0 mg/m <sup>3</sup> R

**ENGINEERING CONTROLS:** Local exhaust ventilation should be utilized when welding, burning, sawing, brazing, grinding, or machining when exposure exceeds occupational exposure limits.

**EYE PROTECTION:** Safety glasses or goggles should be utilized as required by exposure. Other protective equipment should be utilized as required by welding standards.

**SKIN PROTECTION:** Wear appropriate personal protective clothing to prevent skin contact with copper dusts and mists.

# MATERIAL SAFETY DATA SHEET

## COPPER-NICKEL-ZINC ALLOYS 731, 733, 742, 752, 758, 762, 770

Page 4 of 7

**RESPIRATORY PROTECTION:** NIOSH-approved dust or fume respirator should be used to avoid excessive inhalation of particulates when exposure exceeds occupational exposure limits.

**OTHER PREVENTIVE MEASURES:** Do not eat, drink, or smoke during work. Wash hands before eating or smoking.

### 9.0 PHYSICAL AND CHEMICAL PROPERTIES

<b>APPEARANCE:</b>	Salmon-colored, lustrous metal	<b>PHYSICAL STATE:</b>	Solid
<b>ODOR:</b>	None	<b>VAPOR PRESSURE:</b>	Not applicable
<b>PH:</b>	Not applicable	<b>PERCENT VOLATILE:</b>	Not applicable
<b>VAPOR DENSITY (AIR = 1)</b>	Not applicable	<b>SPECIFIC GRAVITY:</b>	8.6 – 8.8
<b>EVAPORATION RATE:</b>	Not applicable	<b>DENSITY, LB/IN<sup>3</sup>:</b>	0.31
<b>SOLUBILITY IN WATER:</b>	Not applicable	<b>MELTING POINT:</b>	1,930 – 2,030 °F
<b>FLASH POINT:</b>	Not applicable	<b>LOWER EXPLOSIVE LIMIT (%):</b>	None
<b>AUTOIGNITION TEMPERATURE:</b>	Not applicable	<b>UPPER EXPLOSIVE LIMIT (%):</b>	None

### 10.0 STABILITY AND REACTIVITY

<b>CHEMICAL STABILITY:</b>	Stable
<b>CONDITIONS TO AVOID:</b>	None
<b>INCOMPATIBLE MATERIALS:</b>	Mercury, ammonia, acetylene acids. Contact with strong acids, bases, or oxidizing agents
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Metallic dust or fumes may be produced during welding, burning, grinding, and machining.
<b>POSSIBILITY OF HAZARDOUS REACTIONS:</b>	Will not occur

### 11.0 TOXICOLOGY INFORMATION

#### ACUTE TOXICITY DATA FOR COMPONENTS

Copper	TDL <sub>o</sub> :	120 µg/kg (human, oral—gastrointestinal effects)
	LD <sub>50</sub> :	0.07 mg/kg (mouse, intraperitoneal)
Nickel	LD <sub>50</sub> :	250 mg/kg (rodent, intraperitoneal)
Zinc	TCL <sub>o</sub> :	124 mg/m <sup>3</sup> / 50 minutes (human, inhalation—respiratory effects)
	LDLo:	388 mg/kg (bird, oral)

# MATERIAL SAFETY DATA SHEET

## COPPER-NICKEL-ZINC ALLOYS 731, 733, 742, 752, 758, 762, 770

Page 5 of 7

### CHRONIC EFFECTS:

Repeated or prolonged overexposure to copper fume may cause the skin and hair to change color.

Hypersensitivity to nickel is common and may cause allergic contact dermatitis, pulmonary asthma, and conjunctivitis.

### 12.0 ECOLOGICAL INFORMATION

Not applicable

### 13.0 DISPOSAL CONSIDERATIONS

#### WASTE DISPOSAL METHODS:

According to local, state, and federal regulations.

### 14.0 TRANSPORT INFORMATION

Not applicable

### 15.0 REGULATORY INFORMATION

#### GLOBAL INVENTORIES

	COPPER	NICKEL	ZINC
TSCA: United States	Included	Included	Included
DSL: Canada	Included	Included	Included
EINECS: European Union:	Included	Included	Included

#### SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):

These alloys are not regulated under Section 302 of SARA and 40 CFR 355.

#### SARA TITLE III SECTION 311/312 HAZARDOUS CATEGORIZATION (40 CFR 370):

OSHA defines these alloys as hazardous under 29 CFR 1910.1200(d).

#### SARA TITLE III SECTION 313 TOXIC CHEMICALS (40 CFR 372):

These alloys may contain the following toxic chemical(s) subject to reporting requirements under this section of SARA and of 40 CFR 372:

COMPONENT	CAS #	% BY WEIGHT
Copper	7440-50-8	53.5 – 73.5
Nickel	7440-02-0	2 – 21

# MATERIAL SAFETY DATA SHEET

## COPPER-NICKEL-ZINC ALLOYS 731, 733, 742, 752, 758, 762, 770

Page 6 of 7

### OTHER LISTS

Chemical Name	CA Prop 65 Chemical	MA Toxic Substance List	MI Critical Materials Register	NJ Hazardous Substances List	PA Right-to-Know List
Copper	No	Yes	Yes	Yes	Yes
Nickel	Yes	Yes	Yes	Yes	Yes
Zinc	No	Yes	Yes	Yes	Yes

### 16.0 OTHER INFORMATION

#### REFERENCES

ACGIH® Threshold Limit Values (TLV®) (2004)

Agency for Toxic Substances and Disease Registry (ATSDR):

Toxicological Profile for Copper, September 2002

Draft Toxicological Profile for Nickel, September 2003

Draft Toxicological Profile for Zinc, September 2003

International Agency for Research on Cancer (IARC) Monographs

National Library of Medicine (NLM) Databases:

ChemID

Integrated Risk Information (IRIS)

International Toxicity Estimates for Risk (ITER)

Chemical Carcinogenesis Risk Information System (CCRIS)

Hazardous Substances Data Bank (HSDB)

National Toxicology Program (NTP) Reports

NIOSH Pocket Guide to Chemical Hazards (2003)

NIOSH/OSHA Occupational Health Guideline for Copper Fume

NIOSH/OSHA Occupational Health Guideline for Copper Dusts and Mists

NIOSH/OSHA Occupational Health Guideline for Nickel Metal and Soluble Nickel Compounds

NIOSH/OSHA Occupational Health Guideline for Zinc Oxide Fume

OSHA General Industry Standards (29 CFR 1910)

Registry of Toxic Effects of Chemical Substances (RTECS®)

# MATERIAL SAFETY DATA SHEET

## COPPER-NICKEL-ZINC ALLOYS 731, 733, 742, 752, 758, 762, 770

Page 7 of 7

### DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

### PREPARATION INFORMATION

Prepared by: Cindy Baldwin, CIH

**Terracon**

5855 Willow Creek Drive SW

Cedar Rapids, Iowa 52404